

*A2  
contd.*  
nail-setting claw hammer head comprising:

a main body disposed along and about a horizontal axis, a vertical axis and a transverse axis which intersect one another perpendicularly at a point of intersection to define a center of mass, the main body having a front surface, a top surface and a rear surface with the rear surface including a nail-head receiving recess formed therein;

an impact member connected to and projecting from the front surface, the impact member having a neck and a hammer face; and

a claw connected to the rear surface of the main body at a first end and forming a fulcrum surface with the top surface, <sup>the</sup> the claw curving about the point of intersection and disposed apart from the rear surface, the claw terminating at a second end opposite the first end with a pair of claw sections defining a V-shaped slot therebetween, the nail-head receiving recess positioned to face the V-shaped slot such that the nail-head receiving recess is sized and adapted to receive the nail head portion of the nail and the V-shaped slot is sized and adapted to receive the shank portion of the nail in order to wedge the shank portion therein.

---

### **REMARKS**

Claims 1-18 are pending in the application. By this Amendment, claims 1 and 10 are amended.

In view of the foregoing, favorable examination on the merits is respectfully requested. Should the Examiner believe anything further is desirable in order to place the application in even better condition for allowance, the Examiner is invited to contact Applicants' representative at the telephone number listed below.